

# OLDSMOBILE

Vehicle Make	Year Range	Manufacturer of Axle	Axle Model	Spline Count	Cover Bolts	Special Notes	POWERTRAX No-Slip Traction System	
							Open	Gov Lock
<b>Cutlass</b>								
Rear Axle								
	1985 - 1988	GM	8.5" rg	28	10	V8	92-0785-2805	
	1978 - 1988	GM	7.5" rg	26	10		92-0775-2605	
	1977	GM	8.875" rg	30	12	V8-396 Eng. Or larger	92-0788-3005	
	1973 - 1977	GM	8.5" rg	28	10		92-0785-2805	
	1973 - 1976	GM	8.875" rg	31		Station Wagon		
	1961 - 1970	GM	8.2" rg	28	10		Spring 2001	
<b>F-85</b>								
Rear Axle								
	1971 - 1972	GM	8.5" rg	28	10		92-0785-2805	
	1969	GM	8.875" rg	30	12		92-0788-3005	
	1967 - 1969	GM	8.2" rg	28	10		Spring 2001	
<b>Starfire</b>								
Rear Axle								
	1975 - 1980	GM	7.5" rg	26	10		92-0775-2605	
	1976 - 1977	GM	6.5" rg					
<b>Sunbird</b>								
Rear Axle								
	1976 - 1980	GM	7.5" rg	26	10		92-0775-2605	
	1976 - 1977	GM	6.5" rg					
<b>Bravado</b>								
Front Axle (see notice at bottom of page)								
	1991 - 2000	GM	7.2" rg	26				
Rear Axle								
	1995 - 2000	GM	8.5" rg	30	10	Z71 OPT/RPO G87	92-0785-3005	
	1991 - 2000	GM	7.625" rg	28	10	4WD V6	92-0776-2805	92-0776-2885

## NOTICE REGARDING ACCURACY OF THIS GUIDE:

Powertrax has attempted to make this Application Guide as accurate as possible. However, Powertrax cannot guarantee correctness. Identical model vehicles may have different axles or differentials than stated in this guide depending on original options ordered and other factors. It is advisable to check the vehicle to determine precisely which differential and axle are present. **IF YOU HAVE ANY QUESTIONS, PLEASE DON'T HESITATE TO CONTACT US AT 800-578-1020.**

## NOTICE REGARDING FRONT AXLE APPLICATIONS:

The Powertrax No-Slip Traction System works well on the front axle of 4-wheel drive vehicles provided a couple of important guidelines are followed. The Powertrax No-Slip Traction System should be used only on vehicles equipped with locking hubs on the front axle or with front axle disconnect. In addition, the vehicle must not be equipped with full time 4-wheel drive. Vehicles equipped with a Powertrax No-Slip Traction System on the front axle should not be operated on the highway with the front hubs locked and 4-wheel drive engaged. Following these guidelines will ensure very on-road driveability while still providing maximum off-road traction.